

DuraMatt Medium Duty Access Mats



Temporary Access Mats



Light Duty



Medium Duty

Description

The DuraMatt Medium Duty Access Mats are designed for short and long term access over hardstanding areas and sensitive grass. The mats provide access for light/medium plant and machinery, but also work personnel and the public.

The mats have been manufactured from 100% Recycled Low Density Polyethylene (LDPE) and 100% recyclable, weight tested to a maximum load of 20 tonnes.

- ✓ Vehicular/Pedestrian traction surface
- ✓ Avoids property, heritage and environmental damage
- ✓ Quick and easy installation
- ✓ Avoids vehicles from getting bogged down

Guide price

£86.50 (excl. VAT)

*We advise checking any agreed or pre-authorised disclaimers on our website before installing or using any of our products, along with live updated and discounted prices available.



We won't be beaten on price - find it cheaper and we'll beat it!

Specifications

 Size	Full size: 2450mm [L] x 1230mm [W] x 12mm [D] Half size: 2400mm [L] x 600mm [W] x 12mm [D] Other sizes available (subject to minimum order quantities)
 Weight	34Kg / 17Kg
 Handholes/connection holes	Full size: 4 handholes and 4 connection holes Half size: 2 handholes and 4 connection holes
 Load	20 tonnes
 Surface	Top: Unique diamond non-slip traction surface Bottom: Smooth surface
 Material	100% Recycled Low Density Polyethylene (LDPE) and 100% recyclable
 Colour	Grey as standard. For more colours, view our DuraMatt Event

The DuraMatt Medium Duty Access Mats flexible nature follows the contours of the ground to help deliver highly effective access over undulating or sloping terrain.

These mats are a better alternative to inadequate materials such as plywood and a long-lasting solution, rather than materials that crack, splinter or break and would be disposed of at the end of a project.



Contact us to find out about products available for hire and finance.

Step 1



Step 2



Step 3



Step 4



[Download MultiMatts Brochure](#)

How to install the DuraMatt Medium Duty Access Mats



Preparation

We recommend grading and levelling ground. A geotextile is also recommended prior to installation.



Installation

The mats have hand holes at each side and should be lifted two people. Please ensure correct manual handling procedures are followed. Each corner has connection points to secure the board into place.



Connection

Use the DuraMatt 2-way, 4-way or Steel Fast Fit Connectors and tighten with standard bolts and oversized washers.