

Portapath™



Event Flooring



Light Duty

Description

Designed with a unique non-slip surface, Portapath is an excellent all-weather, all year-round solution providing an innovative and reliable alternative to traditional flooring systems.

It is durable, lightweight, attractive and affordable, resulting in a perfect surface for any event whatever the size, to protect turf and prevent soil compaction whilst allowing the grass underneath to breathe.

Guide price

£20.65 (excl. VAT)

*We advise checking any agreed or pre-authorised disclaimers on our website before installing or using any of our products, along with live updated and discounted prices available.

- ✓ Lightweight and anti-slip
- ✓ Ventilation slots to allow light and air through
- ✓ Can be laid in any format
- ✓ Wheelchair access and high-heel
- ✓ Easy to clean, maintain and fast to install and dismantle




find it cheaper and we'll beat it!

Specifications

Size	310mm [L] x 80mm [W] x 16mm [H] Supplied in 1m² sections
Weight	3.7Kg per m ²
<u> </u>	Weight tested up to 2 tonnes (depending on ground conditions)
Surface	Anti-slip surface with strong integral 'living hinge'
Material Material	100% High Impact UV Protected Polypropylene from 100% recycled plastic
Colour	Grey, blue or green. Other colours available (subject to minimum order quantities)

The Portapath flooring provides a safe access path for pedestrians and wheelchair users, supporting loads up 2 tonnes.

Designed as a 'custom' system, rolls or panels are available to suit any application and can come in different sizes made to order. Its design allows for quick disconnection and MultiMatts supply a simple separation unit for dismantling large areas.





Contact us to find out about products available for hire and finance.



Step 2





Download MultiMatts Brochure

How to install the Portapath



Preparation

Flat head screwdrivers, rubber mallets, tent pegs and string lines are required to ensure the matting is installed straight.



Installation

Use the string to mark out a line from the bottom right. Roll the tiles out in front and make sure that the clip connectors are on the short end of the adjacent tile. Continue to connect the adjacent lines to the left of the first tiles.



Connection

Apply light foot or hand pressure to join the tiles and lock the connectors into place. Repeat the process until desired area is covered.



















www.multimatts.co.uk