


Vynagrip Anti-slip Resistant Matting is used for a wide range of industrial and commercial matting requirements and is the ideal solution for environments where spillages are likely and to boost productivity in working areas.



 Light Duty

	Size	Standard: 5m [L] x 600mm / 910mm / 1220mm [W] x 15mm [H] Plus: 10m [L] x 600mm / 910mm / 1220mm [W] x 15mm [H]
	Weight	7.6Kg per m ² (may differ slightly depending on size)
	Load	Foot traffic only
	Features	Surface: Diamond cut pattern, two layer open-grid construction Material: Flexible non-porous Polyvinyl Chloride (PVC) Colour: Black, red and blue as standard. Black or black with yellow edging for the Plus version Flammability: EN ISO 13501-1:2007 - Cfl - SI Electrical: insulation resistance > 2000M Ω , electric strength 12,600 volts Anti-Fatigue: ASTM E303 dry/wet with lines along-lines across 87-104/72-88 Temperature: -23°C up to +60°C Acoustic absorption properties
	Storage	Compact, stack on top of each other or roll up
	Accessories	Connector Clips, Snaptracks or PVC Edging

Installation timings



1 person required

 Single line connection in less than 2 mins

 Grid connection in less than 5 mins

Additional information

For detailed description and delivery options, please visit our website at www.multimatts.co.uk/vynagrip-matting

Installation details and visuals are shown in the Product Leaflet.
For alternative products, see categorised items on our website.

Purpose

- ✓ Prevents slipping hazards in environments where accidental spills are made
- ✓ Reduces standing fatigue and boosts productivity
- ✓ Provides high levels of hygiene to resist bacteria growth and mildew

[Order and Deliver](#)

[View Product Leaflet](#)

* We advise checking any agreed or pre-authorised disclaimers on our website before installing or using any of our products.